


1-Line, Uni-directional, Transient Voltage Suppressor



DFN1608-2L

Features

- Ultra small package
- Stand-off voltage: 12V Max
- Transient protection for each line according to IEC61000-4-2(ESD): $\pm 30\text{kV}$ (contact)
- IEC61000-4-5(surge): 55A (8/20 μs)
- Ultra-low capacitance: $C_J = 280\text{ pF typ}$
- Low leakage current
- Low clamping voltage
- RoHS Compliant

Applications


- Power supply protection
- Power management
- Battery Contacts

Mechanical Characteristics

- Package: DFN1608-2L
- Case Material: "Green" Molding Compound.
- Marking Information: See Below



■Definitions of electrical characteristics





ESD12VFPA

■Absolute Maximum Ratings (Ta=25°C unless otherwise specified)

PARAMETER	SYMBOL	Rating	UNIT
Peak pulse power ($t_p = 8/20\mu s$)	P_{pk}	1375	W
Peak pulse current ($t_p = 8/20\mu s$)	I_{PP}	55	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 30	KV
ESD according to IEC61000-4-2 contact discharge		± 30	KV
Junction temperature	T_J	125	°C
Operating temperature	T_{OP}	-40~85	°C
Storage temperature	T_{STG}	-55~150	°C

■Electrical Characteristics (Ta=25°C Unless otherwise specified)

PARAMETER	Symbol	UNIT	Conditions	Min	Typ	Max
Reverse maximum working voltage	V_{RWM}	V				12
Reverse leakage current	I_R	μA	$V_{RWM} = 12V$			1
Reverse breakdown voltage	V_{BR}	V	$I_{BR} = 1mA$	12.5		16
Forward voltage	V_F	V	$I_T = 20mA$	0.25		1.25
Clamping voltage ³⁾	V_{CL}	V	$I_{PP} = 1A, t_p = 8/20\mu s$		13	15
		V	$I_{PP} = 55A, t_p = 8/20\mu s$		20	25
Junction capacitance	C_J	pF	$V_R = 0V, f = 1MHz$ Any I/O pin to GND		280	300

(1). TLP parameter: $Z_0 = 50\Omega$, $t_p = 100ns$, $t_r = 2ns$, averaging window from 60ns to 80ns. R_{DYN} is calculated from 4A to 16A.

(2). Contact discharge mode, according to IEC61000-4-2.

(3). Non-repetitive current pulse, according to IEC61000-4-5.

■Ordering Information (Example)


PREFERED P/N	UNIT WEIGHT(mg)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
SESDULC1E14P5	Approximate 4	3000	30000	120000	Tae& reel




ESD12VFPA

■ Typical Performance Characteristics (Ta=25°C unless otherwise Specified)


8/20μs waveform per IEC61000-4-5




Clamping voltage vs. Peak pulse current




Non-repetitive peak pulse power vs. Pulse time




Contact discharge current waveform per IEC61000-4-2



Capacitance vs. Reverse voltage




Power derating vs. Ambient temperature








TLP Measurement





■ Outline Dimensions



Symbol	Dimensions in Millimeters		
	Min.	Typ.	Max.
A	0.35	0.45	0.55
A1	0.00		0.10
A2	0.15 Ref.		
b	0.56	0.66	0.76
L	0.62	0.72	0.82
L1	0.22	0.32	0.42
D	1.50	1.60	1.70
E	0.70	0.80	0.90
e	0.93BSC		

■ Recommend land pattern (Unit:mm)



UNIT: mm

Notes:

This recommended land pattern is for reference purposes only. Please consult your manufacturing group to ensure your PCB design guidelines are met



Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.