


IGBT Discrete

V_{CE}	650	V
I_C	20	A
$V_{CE(SAT)} I_C=20A$	1.60	V

Circuit



Applications

- Inverter for motor drive
- Air conditioning
- Uninterruptible power supply

Features

- High speed smooth switching device for hard & soft switching
- Maximum junction temperature 175°C
- Positive temperature coefficient
- High short circuit capability(5us)
- High ruggedness, temperature stable

Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-Emitter Breakdown Voltage	V_{CE}	650	V
DC Collector Current, limited by T_{jmax} * $T_C=25^{\circ}C$ $T_C=100^{\circ}C$	I_C	40 20	A
Diode Forward Current, limited by T_{jmax} * $T_C=25^{\circ}C$ $T_C=100^{\circ}C$	I_F	40 20	A
Continuous Gate-Emitter Voltage	V_{GE}	± 20	V
Transient Gate-Emitter Voltage ($t_p \leq 10\mu s, D < 0.010$)	V_{GE}	± 30	V
Turn off Safe Operating Area $V_{CE} \leq 650V$, $T_j \leq 150^{\circ}C$		60	A
Pulsed Collector Current, $V_{GE}=15V$, t_p limited by T_{jmax}	I_{CM}	60	A
Diode Pulsed Current, t_p limited by T_{jmax}	I_{Fpuls}	60	A
Short Circuit Withstand Time, $V_{GE}=15V, V_{CC}=400V, V_{CEM} \leq 650V$	T_{sc}	5	μs
Power Dissipation, $T_j=175^{\circ}C, T_C=25^{\circ}C$	P_{tot}	55	W

* Limited by maximum junction temperature. Applicable for TO220 standard package.



Operating Junction Temperature	T_j	-40...+175	°C
Storage Temperature	T_s	-55...+150	°C
Soldering Temperature, wave soldering 1.6mm (0.063in.) from case for 10s		260	°C

Electrical Characteristics of the IGBT ($T_j = 25^\circ\text{C}$ unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Collector-Emitter Breakdown Voltage	BV_{CES}	$V_{GE}=0V, I_C=1mA$	650		-	V
Gate Threshold Voltage	$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C=250\mu A$	4.0	5.0	6.5	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$V_{GE}=15V, I_C=20A$ $T_j=25^\circ\text{C},$ $T_j=125^\circ\text{C}$ $T_j=150^\circ\text{C}$		1.60 1.80 1.90	1.90	V
Zero Gate Voltage Collector Current	I_{CES}	$V_{CE}=650V, V_{GE}=0V$ $T_j=25^\circ\text{C},$ $T_j=150^\circ\text{C}$			1 5	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}=0V, V_{GE}= \pm 20V$			± 200	nA

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic						
Input Capacitance	C_{ies}	$V_{CE}=25V, V_{GE}=0V,$ $f=1MHz$	-	1.05	-	nF
Reverse Transfer Capacitance	C_{res}		-	0.02	-	
Gate Charge	Q_G	$V_{CC}=300V, I_C=20A,$ $V_{GE}=15V$	-	0.09	-	uC

**Electrical Characteristics of the Diode** ($T_j = 25^\circ\text{C}$ unless otherwise specified):

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Static						
Diode Forward Voltage	V_F	$I_F = 20\text{A}$ $T_j = 25^\circ\text{C}$, $T_j = 125^\circ\text{C}$ $T_j = 150^\circ\text{C}$		1.75 1.65 1.60	2.30	V

Switching Characteristic, Inductive Load

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T _j = 25℃						
Turn-on Delay Time	t _{d(on)}	T _j =25℃ V _{CC} = 300V, I _C =20A, V _{GE} =-5V~15V, R _g =20Ω	-	46	-	ns
Rise Time	t _r		-	47	-	ns
Turn-on Energy	E _{on}		-	0.36	-	mJ
Turn-off Delay Time	t _{d(off)}		-	80	-	ns
Fall Time	t _f		-	74	-	ns
Turn-off Energy	E _{off}		-	0.25	-	mJ
Dynamic , at T _j = 125℃						
Turn-on Delay Time	t _{d(on)}	T _j =125℃ V _{CC} = 300V, I _C =20A, V _{GE} =-5V~15V, R _g =20Ω	-	39	-	ns
Rise Time	t _r		-	53	-	ns
Turn-on Energy	E _{on}		-	0.39	-	mJ
Turn-off Delay Time	t _{d(off)}		-	95	-	ns
Fall Time	t _f		-	131	-	ns
Turn-off Energy	E _{off}		-	0.37	-	mJ
Dynamic , at T _j = 150℃						
Turn-on Delay Time	t _{d(on)}	T _j =150℃ V _{CC} = 300V, I _C =20A, V _{GE} =-5V~15V, R _g =20Ω	-	40	-	ns
Rise Time	t _r		-	55	-	ns
Turn-on Energy	E _{on}		-	0.41	-	mJ
Turn-off Delay Time	t _{d(off)}		-	95	-	ns
Fall Time	t _f		-	138	-	ns
Turn-off Energy	E _{off}		-	0.40	-	mJ











Electrical Characteristics of the DIODE





Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Dynamic , at T _j = 25°C						
Reverse Recovery Current	I _{rr}	I _F =20A, V _R =300V, -di/dt= 360A/μs,	-	6	-	A
Diode reverse recovery time	trr		-	200	-	ns
Reverse Recovery Charge	Q _{rr}		-	0.25	-	uC
Reverse Recovery Energy	E _{rec}		-	0.07	-	mJ
Dynamic , at T _j = 125°C						
Reverse Recovery Current	I _{rr}	I _F =20A, V _R =300V, -di/dt= 360A/μs,	-	8	-	A
Diode reverse recovery time	trr		-	218	-	ns
Reverse Recovery Charge	Q _{rr}		-	0.59	-	uC
Reverse Recovery Energy	E _{rec}		-	0.13	-	mJ
Dynamic , at T _j = 150°C						
Reverse Recovery Current	I _{rr}	I _F =20A, V _R =300V, -di/dt= 360A/μs,	-	9	-	A
Diode reverse recovery time	trr		-	227	-	ns
Reverse Recovery Charge	Q _{rr}		-	0.78	-	uC
Reverse Recovery Energy	E _{rec}		-	0.16	-	mJ





Thermal Resistance

Parameter	Symbol	Max. Value	Unit
IGBT Thermal Resistance, Junction - Case	R _{th(j-c)}	2.7	K/W
Diode Thermal Resistance, Junction - Case	R _{th(j-c)}	4.8	K/W
Thermal Resistance, Junction - Ambient	R _{th(j-a)}	40	K/W











● Circuit Diagram



● Package Outline Information

CASE: TO-220F package information



SYMBOL	单位: mm			SYMBOL	单位: mm			SYMBOL	单位: mm		
	MIN	NOM	MAX		MIN	NOM	MAX		MIN	NOM	MAX
A	4.40	4.50	4.60	E	10.00	10.16	10.30	ΦP2	3.30	3.40	3.50
A1	2.34	2.54	2.74	E1	9.94	10.06	10.20	θ1	3°	5°	7°
A2	2.66	2.76	2.86	E2	9.40	9.50	9.60	θ2	42°	45°	48°
A3	1.0REF			F1	1.40	1.50	1.60				
b1	1.18	1.20	1.24	F2	13.80	13.90	14.00				
b2	0.75	0.80	0.85	F3	3.20	3.30	3.40				
b3	1.22	1.30	1.38	G1	6.90	7.00	7.10				
C	0.45	0.50	0.55	K1	0.65	0.70	0.75				
D	15.67	15.87	16.07	L	12.78	12.98	13.18				
D1	9.04	9.12	9.20	L1	3.40	3.50	3.60				
e	2.50	2.54	2.58	Q	6.50REF						
e1	5.08REF			ΦP	3.08	3.18	3.28				



Disclaimer

The information presented in this document is for reference only. This publication is made by Yangzhou Yangjie Electronic Technology Co., Ltd. , our company reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The data provided in this specification comes from professional testing equipment of Yangjie Electronic Laboratory, not general testing equipment. All the data is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

IGBTs is the device which is sensitive to the static electricity, it is necessary to protect the device from being damaged by the static electricity when using it.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.