






## P-Channel Enhancement Mode Field Effect Transistor



**SOT-23**



### Product Summary

• $V_{DS}$	-30V
• $I_D$	-4.1A
• $R_{DS(on)}$ (at $V_{GS}=-10V$ )	<47mΩ
• $R_{DS(on)}$ (at $V_{GS}=-4.5V$ )	<65mΩ

### General Description

- Low  $R_{DS(on)}$  & FOM
- Extremely low switching loss
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free
- Part no. with suffix "Q" means AEC-Q101 qualified

### Applications

- Power management
- Portable equipment

### Absolute Maximum Ratings ( $T_A=25^\circ C$ unless otherwise noted)

Parameter		Symbol	Limit	Unit
Drain-source Voltage		$V_{DS}$	-30	V
Gate-source Voltage		$V_{GS}$	$\pm 20$	V
Drain Current	$T_A=25^\circ C$	$I_D$	-4.1	A
	$T_A=100^\circ C$		-2.5	
Pulsed Drain Current <sup>A</sup>		$I_{DM}$	-20	A
Total Power Dissipation <sup>B</sup>	$T_A=25^\circ C$	$P_D$	1.2	W
	$T_A=100^\circ C$		0.47	
Junction and Storage Temperature Range		$T_J, T_{STG}$	-55~+150	°C

### Thermal resistance

Parameter		Symbol	Typ	Max	Units
Thermal Resistance Junction-to-Ambient <sup>C</sup>	Steady-State	$R_{\theta JA}$	80	105	°C/W

### Ordering Information (Example)

PREFERRED P/N	PACKING CODE	Marking	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
YJL3407CQ	F2	3407C.	3000	30000	120000	7" reel

■ Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)

Parameter	Symbol	Conditions	Min	Typ	Max	Units
<b>Static Parameter</b>						
Drain-Source Breakdown Voltage	$\text{BV}_{\text{DSS}}$	$V_{\text{GS}}=0\text{V}, I_{\text{D}}=-250\mu\text{A}$	-30			V
Zero Gate Voltage Drain Current	$I_{\text{DSS}}$	$V_{\text{DS}}=-30\text{V}, V_{\text{GS}}=0\text{V}$			-1	$\mu\text{A}$
Gate-Body Leakage Current	$I_{\text{GSS}}$	$V_{\text{GS}}=\pm20\text{V}, V_{\text{DS}}=0\text{V}$			$\pm100$	nA
Gate Threshold Voltage	$V_{\text{GS}(\text{th})}$	$V_{\text{DS}}=V_{\text{GS}}, I_{\text{D}}=-250\mu\text{A}$	-1	-1.5	-2.4	V
Static Drain-Source On-Resistance	$R_{\text{DS}(\text{ON})}$	$V_{\text{GS}}=-10\text{V}, I_{\text{D}}=-4.1\text{A}$		35	47	$\text{m}\Omega$
		$V_{\text{GS}}=-4.5\text{V}, I_{\text{D}}=-3.5\text{A}$		50	65	$\text{m}\Omega$
Diode Forward Voltage	$V_{\text{SD}}$	$I_{\text{S}}=-4.1\text{A}, V_{\text{GS}}=0\text{V}$			-1.2	V
Gate resistance	$R_{\text{G}}$	f=1MHz		17.5		$\Omega$
<b>Dynamic Parameters</b>						
Input Capacitance	$C_{\text{iss}}$	$V_{\text{DS}}=-15\text{V}, V_{\text{GS}}=0\text{V}, f=1\text{MHz}$		471		pF
Output Capacitance	$C_{\text{oss}}$			84		
Reverse Transfer Capacitance	$C_{\text{rss}}$			69		
<b>Switching Parameters</b>						
Total Gate Charge	$Q_{\text{g}}$	$V_{\text{GS}}=-10\text{V}, V_{\text{DS}}=-15\text{V}, I_{\text{D}}=-4.1\text{A}$	-	9	-	nC
Gate-Source Charge	$Q_{\text{gs}}$		-	1.5	-	
Gate-Drain Charge	$Q_{\text{gd}}$		-	2.3	-	
Reverse Recovery Charge	$Q_{\text{rr}}$	$I_{\text{F}}=-4.1\text{A}, \text{di}/\text{dt}=100\text{A/us}$	-	12	-	nC
Reverse Recovery Time	$t_{\text{rr}}$		-	32	-	ns
Turn-on Delay Time	$t_{\text{D}(\text{on})}$		-	9	-	ns
Turn-on Rise Time	$t_{\text{r}}$	$V_{\text{GS}}=-10\text{V}, V_{\text{DD}}=-15\text{V}, I_{\text{D}}=-4.1\text{A}$ $R_{\text{GEN}}=2.5\Omega$		3		
Turn-off Delay Time	$t_{\text{D}(\text{off})}$			29		
Turn-off fall Time	$t_{\text{f}}$			15		

A. Repetitive rating; pulse width limited by max. junction temperature.

B.  $P_d$  is based on max. junction temperature, using junction-ambient thermal resistance.C. The value of  $R_{\thetaJA}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in the still air environment with  $T_A=25^\circ\text{C}$ .

The maximum allowed junction temperature of 150°C. The value in any given application depends on the user's specific board design.







**■Typical Electrical and Thermal Characteristics Diagrams**


Figure 5. On-Resistance vs Gate to Source Voltage

Figure 6. Normalized On-Resistance




Figure 7. RDS(on) VS Drain Current




Figure 8. Forward characteristics of reverse diode




Figure 9. Normalized breakdown voltage




Figure 10. Normalized Threshold voltage




Figure 11. Current dissipation




Figure 12. Power dissipation




Figure 13. Maximum Transient Thermal Impedance





Figure 14. Safe Operation Area

**■ SOT-23 Package information**

SYMBOL	DIMENSIONS			
	INCHES		Millimeter	
	MIN.	MAX.	MIN.	MAX.
A	0.035	0.045	0.900	1.150
A1	0.000	0.004	0.000	0.100
A2	0.035	0.041	0.900	1.050
b	0.012	0.020	0.300	0.500
c	0.004	0.008	0.100	0.200
D	0.110	0.118	2.800	3.000
E	0.047	0.055	1.200	1.400
E1	0.089	0.100	2.250	2.550
e	0.037TYP		0.950TYP	
e1	0.071	0.079	1.800	2.000
L	0.022REF		0.550REF	
L1	0.012	0.020	0.300	0.500
theta	0°	8°	0°	8°

## NOTE:

1.PACKAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.

2.TOLERANCE 0.1mm UNLESS OTHERWISE SPECIFIED.

3.THE PAD LAYOUT IS FOR REFERENCE PURPOSES ONLY.



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military. Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website <http://www.21yangjie.com>, or consult your nearest Yangjie's sales office for further assistance.