


## Silicon Carbide Power MOSFET (N-Channel Enhancement)

|              |       |
|--------------|-------|
| $V_{DS}$     | 1200V |
| $I_D$ (25°C) | 67A   |
| $R_{DS(on)}$ | 34mΩ  |



### Features

- High speed switching
- Essentially no switching losses
- Reduction of heat sink requirements
- Maximum working temperature at 175 °C
- High blocking voltage
- Fast Intrinsic diode with low recovery current
- High-frequency operation
- Halogen free, RoHS compliant

### Typical Applications

Typical applications are in power factor correction(PFC), solar inverter, uninterruptible power supply, motor drives, photovoltaic inverter, electric car and charger.

### Mechanical Data

- **Package:** TO-247-4L
- **Terminals:** Tin plated leads
- **Polarity:** As marked

### ■Maximum Ratings ( $T_c=25^\circ\text{C}$ Unless otherwise specified)

| PARAMETER                                          | SYMBOL          | UNIT             | VALUE         | TEST CONDITIONS                                  | NOTE   |
|----------------------------------------------------|-----------------|------------------|---------------|--------------------------------------------------|--------|
| Device marking code                                |                 |                  | D212040NCFYG3 |                                                  |        |
| Drain source voltage<br>@ $T_j=25^\circ\text{C}$   | $V_{DS,max}$    | V                | 1200          | $V_{GS}=0V, I_D=100\mu A$                        |        |
| Gate source voltage<br>@ $T_j=25^\circ\text{C}$    | $V_{GS,max}$    | V                | -8/+22        | Absolute maximum values                          |        |
| Gate source voltage<br>@ $T_j=25^\circ\text{C}$    | $V_{GS,op}$     | V                | -4/+18        | Recommended operational values                   |        |
| Continuous drain current @ $T_c=25^\circ\text{C}$  | $I_D$           | A                | 67            | $V_{GS}=18V, T_c=25^\circ\text{C}$               | Fig.17 |
| Continuous drain current @ $T_c=100^\circ\text{C}$ |                 |                  | 46            | $V_{GS}=18V, T_c=100^\circ\text{C}$              |        |
| Pulsed drain current                               | $I_{D(pulsed)}$ | A                | 180           | Pulse width $t_p$ limited by $T_{j,max}$         | Fig.22 |
| Avalanche energy,Single Pulse                      | $E_{AS}$        | mJ               | 785           | $V_{DD}=75V, L=30mH$                             |        |
| Power Dissipation                                  | $P_{TOT}$       | W                | 333           | $T_c=25^\circ\text{C}, T_j = 175^\circ\text{C}$  | Fig.16 |
| Power Dissipation                                  |                 |                  | 165           | $T_c=100^\circ\text{C}, T_j = 175^\circ\text{C}$ |        |
| Operating junction and Storage temperature range   | $T_j, T_{stg}$  | $^\circ\text{C}$ | -55 to +175   |                                                  |        |
| Soldering temperature                              | $T_L$           | $^\circ\text{C}$ | 260           | 1.6mm (0.063") from case for 10s                 |        |
| Mounting torque                                    | $T_M$           | Nm               | 0.6           | M3 screw Maximum of mounting process: 3          |        |



# YJD212040NCFYG3

## ■Static Electrical Characteristics (Tc=25°C unless otherwise specified)

| PARAMETER                                | SYMBOL        | UNIT | Min. | Typ. | Max. | Test Conditions                                  | Note        |
|------------------------------------------|---------------|------|------|------|------|--------------------------------------------------|-------------|
| Gate threshold voltage                   | $V_{GS(th)}$  | V    | 2.0  | 3.0  | 4.0  | $V_{DS}=V_{GS}$ , $I_D=12mA$                     | Fig.4, 11   |
|                                          |               |      |      | 2.2  |      | $V_{DS}=V_{GS}$ , $I_D=12mA$ , $T_j=175^\circ C$ |             |
| Drain source breakdown voltage           | $V_{(BR)DSS}$ | V    | 1200 |      |      | $V_{GS}=0V$ , $I_D=100\mu A$                     |             |
| Gate source leakage current              | $I_{GSS}$     | nA   |      | 10   | 100  | $V_{GS}=18V$ , $V_{DS}=0V$                       |             |
| Current drain source on-state resistance | $R_{DS(on)}$  | mΩ   |      | 34   | 42   | $V_{GS}=18V$ , $I_D=30A$                         | Fig.5, 6, 7 |
|                                          |               |      |      | 56   |      | $V_{GS}=18V$ , $I_D=30A$ , $T_j=175^\circ C$     |             |
| Transconductance                         | $g_f$         | S    |      | 19   |      | $V_{DS}=20V$ , $I_D=30A$                         | Fig.4       |
|                                          |               |      |      | 18   |      | $V_{DS}=20V$ , $I_D=30A$ , $T_j=175^\circ C$     |             |

## ■Dynamic Electrical Characteristics (Tc=25°C unless otherwise specified)

| PARAMETER                | SYMBOL    | UNIT | Min. | Typ. | Max. | Test Conditions                                                               | Note       |
|--------------------------|-----------|------|------|------|------|-------------------------------------------------------------------------------|------------|
| Input capacitance        | $C_{iss}$ | pF   |      | 3362 |      | $V_{DS}=1000V$ , $V_{GS}=0V$ , $T_j=25^\circ C$ ,<br>$f=1MHz$ , $V_{AC}=25mV$ | Fig.13, 14 |
| Output capacitance       | $C_{oss}$ |      |      | 119  |      |                                                                               |            |
| Reverse capacitance      | $C_{rss}$ |      |      | 5.4  |      |                                                                               |            |
| Coss stored energy       | $E_{oss}$ | uJ   |      | 85   |      |                                                                               | Fig.15     |
| Gate source charge       | $Q_{gs}$  | nC   |      | 31   |      | $V_{DS}=1000V$ , $V_{GS}=-4/18V$ , $I_D=30A$                                  | Fig.12     |
| Gate drain charge        | $Q_{gd}$  |      |      | 58   |      |                                                                               |            |
| Gate charge              | $Q_g$     |      |      | 117  |      |                                                                               |            |
| Internal gate resistance | $R_g$     | Ω    |      | 1.6  |      | $f=1MHz$                                                                      |            |

## ■Switching Characteristics (Tc=25°C unless otherwise specified)

| PARAMETER                 | SYMBOL       | UNIT | Min. | Typ. | Max. | Test Conditions                                                                   | Note       |
|---------------------------|--------------|------|------|------|------|-----------------------------------------------------------------------------------|------------|
| Turn on switching energy  | $E_{on}$     | uJ   |      | 363  |      | $V_{DD}=1000V$ , $V_{GS}=-4/+18V$ , $I_D=30A$ ,<br>$R_g=2.4\Omega$ , $L=100\mu H$ | Fig.19, 20 |
| Turn off switching energy | $E_{off}$    |      |      | 95   |      |                                                                                   |            |
| Turn on delay time        | $t_{d(on)}$  | ns   |      | 11   |      | $V_{DD}=1000V$ , $V_{GS}=-4/+18V$ , $I_D=30A$ ,<br>$R_g=2.4\Omega$ , $L=100\mu H$ | Fig.21     |
| Rise time                 | $t_r$        |      |      | 17   |      |                                                                                   |            |
| Turn off delay time       | $t_{d(off)}$ | ns   |      | 28   |      |                                                                                   |            |
| Fall time                 | $t_f$        |      |      | 11   |      |                                                                                   |            |



## ■Body diode characteristics (T<sub>c</sub>=25°C unless otherwise specified )

| PARAMETER                        | SYMBOL           | UNIT | Min. | Typ. | Max. | Test Conditions                                                                 | Note  |
|----------------------------------|------------------|------|------|------|------|---------------------------------------------------------------------------------|-------|
| Diode forward voltage            | V <sub>SD</sub>  | V    |      | 4.7  |      | V <sub>GS</sub> =-4V, I <sub>SD</sub> =15A                                      | Fig.8 |
|                                  |                  |      |      | 3    |      | V <sub>GS</sub> =0V, I <sub>SD</sub> =15A, T <sub>j</sub> =175°C                | Fig.9 |
| Continuous diode forward current | I <sub>S</sub>   | A    |      | 65   |      | T <sub>c</sub> =25°C                                                            |       |
| Reverse recovery time            | t <sub>rr</sub>  | nS   |      | 17   |      | V <sub>R</sub> =800V, V <sub>GS</sub> =-4V, I <sub>D</sub> =30A, di/dt=2000A/uS |       |
| Reverse recovery charge          | Q <sub>rr</sub>  | nC   |      | 178  |      |                                                                                 |       |
| Peak reverse recovery current    | I <sub>rrm</sub> | A    |      | 16   |      |                                                                                 |       |

## ■Thermal Characteristics (T<sub>a</sub>=25°C Unless otherwise specified )

| PARAMETER          | SYMBOL            | UNIT | Typ. |
|--------------------|-------------------|------|------|
| Thermal resistance | R <sub>θJ-C</sub> | °C/W | 0.45 |

## ■Typical Characteristics




Figure 1. Output Characteristics T<sub>j</sub> = -55°C




Figure2. Output Characteristics T<sub>j</sub> = 25°C




Figure 3. Output Characteristics  $T_j = 175^\circ\text{C}$




Figure 4. Transfer Characteristics for Various Junction Temperature




Figure 5. On-resistance vs. Temperature for Various Gate Voltage




Figure 6. Normalized on-resistance vs. Temperature




Figure 7. On-resistance vs. Drain Current




Figure 8. Body Diode Characteristic at  $T_j = 25^\circ\text{C}$




Figure 9. Body Diode Characteristic




Figure 10. 3<sup>rd</sup> quadrant Characteristic at Tj= 25 °C




Figure 11. Threshold Voltage vs. Temperature




Figure 12. Gate Charge Characteristic




Figure 13. Capacitances vs. Drain Source Voltage (0-1000V)




Figure 14. Capacitances vs. Drain Source Voltage (0-200V)




Figure 15. Output Capacitor Stored Energy




Figure 16. Maximum Power Dissipation Derating vs. Case Temperature




Figure 17. Continuous Drain Current Derating vs. Case Temperature




Figure 18. Transient Thermal Impedance (Junction - Case)




Figure 19. Clamped Inductive Switching Energy vs. Drain Current




Figure 20. Clamped Inductive Switching Energy vs. R<sub>g</sub>




Figure 21. Switching Times vs.  $R_g$




Figure 22. Safe Operating Area




Figure 23. Switching Times Definition





Figure 24. Clamped Inductive Switching Waveform Test Circuit

## ■Outline Dimensions



| TO247-4L |         |       |       |
|----------|---------|-------|-------|
| Dim      | Min     | Norm  | Max   |
| A        | 4.80    | 5.00  | 5.20  |
| A1       | 2.30    | 2.40  | 2.50  |
| A2       | 1.88    | 1.98  | 2.08  |
| b        | 1.10    | 1.20  | 1.30  |
| b1       | 1.20    | /     | 1.50  |
| b2       | 2.35    | 2.55  | 2.75  |
| b3       | 2.45    | /     | 2.85  |
| c        | 0.55    | 0.60  | 0.65  |
| D        | 23.3    | 23.45 | 23.6  |
| D1       | 16.25   | 16.55 | 16.85 |
| D2       | 1.00    | /     | 1.30  |
| e        | TYP2.54 |       |       |
| e1       | TYP5.06 |       |       |
| E        | 15.75   | 15.90 | 16.05 |
| E1       | 13.80   | /     | 14.20 |
| E2       | 4.40    | 4.75  | 5.10  |
| E3       | 13.00   | /     | 13.45 |
| L        | 17.34   | 17.49 | 17.64 |
| L1       | 4.00    | /     | 4.30  |
| L2       | 2.35    | /     | 2.65  |
| L3       | TYP1.98 |       |       |
| Q        | 5.60    | 5.80  | 6.00  |
| S        | 6.05    | /     | 6.30  |
| p        | TYP3.58 |       |       |
| p1       | TYP7.18 |       |       |
| p2       | TYP3.00 |       |       |



## Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with ordinary electronic equipment or devices, and not designed to be used with equipment or devices which require high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.